

BuPAD




Dual LED Blue/White Light Transilluminator


Description

The BluPAD, as an innovatively designed transilluminator with dual light sources, is applicable in various Life Sciences research areas for observing and analyzing the nucleic acids and proteins. Given its most optimal and humanized design for the post-observation applications, such as gel cutting and data imaging and filing, it is desired to provide the researchers with a brand-new comfortable, convenient, and safe experience.

Blue Light mode



Using a 470 nm LED wavelength as the excitation source, the Blue Light mode is designed for qualitative and quantitative analysis of nucleic acid and protein experiments using fluorescent staining reagents. In addition to being fully compatible with our safe reagents like Prime Juice, Novel Green Plus, and the OmniPCR series, it also works exceptionally well with most fluorescent stains on the market, including SYBR Gold, SYBR Green I and II, SYPRO Ruby, SYPRO Orange, Coomassie Fluor Orange, GelStar, and GelGreen.




The three-level adjustable light intensity feature lets users fine-tune contrast based on sample concentration to get the best possible imaging quality. Furthermore, the hingeless magnetic amber filter provides a simple, safe, and convenient way to open and close the unit during operation.

Figure 1.

◀ Excitation and Emission Spectra for BluPAD Dual LED Blue/White Light Transilluminator

White Light mode



By using the whole-wavelength white LED light as the excitation light source, the White Light mode exhibits softness and uniformity and is applicable for observing or imaging the SDS-PAGE gels that are stained with the Coomassie Blue or Silver Stain. It can also be employed as a simple film-viewing transilluminator for checking the X-Ray film for the research or clinical purpose. With the light intensity adjustment function, the contrasting adjustment of the light intensity is enabled at three levels according to the observational requirements for achieving the best imaging quality.

Field Study Mode

Connectable with the external power bank for the hassle-free field experiments.

**The power bank is NOT INCLUDED in the package and needs to be purchased by the user.

Features

- ① Amber Filter
- ② Designer Metal Housing
- ③ Bottom Up Light
- ④ Adjustable Light Intensity (3 Levels)
- ⑤ Enhanced Portability with the Power Bank

Dual Light Sources

LED White Light and Blue Light

Broad ranges of applicability and compatibility in basic science and medical diagnosis research fields.

Magnetic Filter

The hinges-free design offers simplicity, safety, and convenience to the user and will not cause any damage to the filter near the hinges. Conducting the observation and gel-cutting does not require the protective goggles.

Bottom-Up LED Illumination

It prevents the interference from the reflective lights that are caused by the side illumination, thus improving the observational and imaging quality. Since the LED lights are enduring and safe, it does not cause damage to the eyes and skin or to the experiment sample as normally found with the UV illumination.

Adjustable Light Intensity (3 Levels)

Adjusting the light intensity and contrast based on the sample quantity or observational requirement will achieve the best observational or imaging quality.

5mins Automatic Power-Off

It protects the transilluminator from the risk that is caused by the user's operational negligence.

Designer Metal Housing

The transilluminator's base is rendered more stable, thus facilitating the operational process.


Exquisite and Compact Design

It offers the ease of mobility and storage and is suitable for the experimental observation during the field study.

Enhanced Portability with the Power Bank

Hassle-free for performing the outdoor experiment.

****The power bank is NOT INCLUDED in the package and needs to be purchased by the user.**



Specifications

Unit Dimensions(WxLxH)	18.5 x 22 x 3cm
Gel Viewing Dimensions(WxL)	12 x 18cm
Input Voltage	100-240Vac
Input Current	2.0A
LED Source	Built-in blue light & white light LED module
LED life(hours)	>30,000
Emission maxima(nm)	470 nm
Store temperature	25°C
Automatic Power-Off	5 mins
Filter Type	Amber filter (580 nm)
Certifications	CE/ETL/cETL
Patent	TW: M543442 / CN: No. 6773227

**This product incorporates Clare Chemical Research, Inc's, Dark Reader® transilluminator technology.

Related Ordering Information

Cat. No.	Description
BP001MIC-2	BluPAD Dual LED Blue/White Light Transilluminator
BP001mDR-N2	BluPAD miniDarkroom
BP001KNIFE-N	BluPAD Gel-Cutting Knife
BP001AFC-P3	BluPAD Upper amber filter cover
BP001WUPM	BluPAD white uniform plate
BP001BDPGM	BluPAD Blue uniform plate w glass
BP001AP	BluPAD 60 watt adaptor



Manufacturer

BIO-HELIX
CO., LTD.

Bio-Helix Co., Ltd.

5F., No. 145, Sec. 3, Beixin Rd., Xindian Dist. New Taipei City 231030, Taiwan

Tel: +886-2-24624956

E-mail: info@bio-helix.com



www.bio-helix.com



UVPAD Trio LED 365/302/300nm UV Transilluminator

Website



PROTOCOL



FEATURES

- Trio UV Wavelengths at 300 nm, 302 nm and 365 nm
- Magnetic Lid Design
- Auto Power-Off When Lid Is Detached
- Bottom-Illumination LED Design
- Three-Level Brightness Adjustment
- Automatic Shut-Off Function
- Designer Metal Housing
- Exquisite and Compact Design

SPECIFICATIONS

Unit Dimensions : (W × L × H) : 23.0 × 20.1 × 5.1 cm

Viewing Area (W × L): 365 nm / 302 nm Modes: 21.0 × 13.0 cm
300 nm Mode : 12.0 × 10.0 cm

Power Adapter Input : 100–240 VAC ±10%, 50/60 Hz, 1.5-0.8A

Output : 24V DC, 2.5A (60W)

LED Light : Source Built-in UV 365 nm, UV 302 nm, and UV 300 nm LED modules


LED Lifespan : >5,000 hours

Emission Wavelengths : 365 nm / 302 nm / 300 nm


Auto Power-Off Time : 365 nm / 302 nm Modes: 5 minutes
High-Power 300 nm Mode: 7 minutes

Filter Type : UV-blocking Polycarbonate

Certifications : CE / ETL



The trademark holders are not affiliated with Bio-Helix Co., Ltd.
and Bio-Helix does not endorse these products.



High-power 300 nm enables rapid
protein visualization in UV-activated
polyacrylamide gels